

# CONQUER

## Surface Mount Fuse

### Type SEI(G)

Slow Blow Fuse Series



SEI(G)



#### Electrical Characteristic

Rated Current	1 In	2.5 In
	MIN	MAX
500mA~5A	4 hr	120 sec

#### Interrupting Rating

50 amperes at 250V AC

#### Operating Temperature

-55°C to +125°C

#### Physical Specification

##### Material

Body: Ceramic

Terminations: Gold Plated Brass Caps

##### Packaging

Rating	Packaging Option	Packaging Specification	Quantity
500mA~5A	24mm Tape and Reel	EIA RS-481-2	2500

Catalog Number	Ampere Rating [ In ]	Voltage Rating ( V )	Interrupting Rating	Nominal Resistance Cold Ohms	Nominal Melting I <sup>2</sup> t A <sup>2</sup> Sec
SEI.500	500mA	250V	50A@250V AC	0.5479	1.963
SEI.750	750mA			0.2600	3.375
SEI 001	1A			0.1800	11.22
SEI 1.50	1.5A			0.1027	14.85
SEI 002	2A			0.0504	19.84
SEI 2.50	2.5A			0.0370	20.50
SEI 003	3A			0.0280	54.00
SEI 3.50	3.5A			0.0199	57.82
SEI 004	4A			0.0158	125.6
SEI 005	5A			0.0120	185.0

#### Mechanical Dimension

500mA~5A:

